Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200



01/05/2023

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier 9140A0 Revision Date: 03/06/2024

Product Name: EPOPLEX LS60 WHITE

1.2 Relevant identified uses of the substance or mixture and uses

advised against

Advised against: others than recommended

1.3 Details of the supplier of the safety data sheet

Manufacturer: EPOPLEX, A DIVISION OF STONCOR GROUP, INC

1000 EAST PARK AVENUE MAPLE SHADE, NJ 08052

+1 856 7797500 (US)

Datasheet Produced by: ehs@stonhard.com

1.4 Emergency telephone number: +1 703-741-5970 - North America

+1 800-424-9300

+55 11 4349 1359 - South America +52 55 8526 4930 - Central America

+44 20 3885 0382 - Middle East, Eastern Europe, Western Europe, and Africa

Supersedes Date:

+65 3163 8374 - Asia, South Asia, And Oceania

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 3
Hazardous to the aquatic environment, Chronic, category 2
Carcinogenicity, category 2
Eye Irritation, category 2A
Skin Irritation, category 2
Skin Sensitizer, category 1
STOT, single exposure, category 3, RTI

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

Benzyl alcohol, titanium dioxide, PHENOL, 4,4'-(1-METHYLETHYLIDENE) BIS-, POLYMER WITH (CHLOROMETHYL) OXIRANE

HAZARD STATEMENTS

Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2A	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 3	H331	Toxic if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Carcinogenicity, category 2	H351	Suspected of causing cancer.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.

PRECAUTION PHRASES

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/ face protection.
P284	Wear respiratory protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+313 P333+313 P391	IF exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Collect spillage.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

OXIRANE

Hazardous ingredients

METHYLETHYLIDENE) 11 2, Skin Irrit. 2, Skin Sens.	Name According to EEC	EINEC No.	<u>CAS-No.</u>	<u>%</u>	<u>Classifications</u>	
(CHLOROMETHYL)	METHYLETHYLIDENE) BIS-, POLYMER WITH	500-033-5	25068-38-6	50 - <75	H315-317-319-335-4 11	Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3 RTI

titanium dioxide	236-675-5	13463-67-7	10 - <25	H351	Carc. 2
Benzyl alcohol	202-859-9	100-51-6	2.5 - <10	H302-312-319-331	Acute Tox. 3 Inhalation, Acute Tox. 4 Dermal, Acute Tox. 4 Oral, Eye Irrit. 2

CAS-No.

M-Factors

25068-38-6 13463-67-7 100-51-6

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to skin. May cause sensitization by skin contact. Prolonged or repeated exposure increases the risk. Harmful to aquatic organisms.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Contains epoxy constituents. See information supplied by the manufacturer.

Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. May cause long-term adverse

effects in the aquatic environment.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Extremes of temperature and direct sunlight.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(US)

<u>Name</u>	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
PHENOL, 4,4'-(1- METHYLETHYLIDENE) BIS-, POLYMER WITH (CHLOROMETHYL OXIRANE	25068-38-6			
titanium dioxide	13463-67-7	10 MGM3 10 MGM3		
Benzyl alcohol	100-51-6			

<u>Name</u> CAS-NO. <u>OSHA PEL</u> <u>OSHA ST</u>	Name	CAS-No. OSI	<u>HA PEL</u> <u>OSHA STE</u>
--	------	-------------	-------------------------------

25068-38-6

PHENOL, 4,4'-(1-

METHYLETHYLIDENE) BIS-,

POLYMER WITH (CHLOROMETHYL)

OXIRANE

titanium dioxide 13463-67-7 15 MGM3

Benzyl alcohol 100-51-6

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Respirator with filter for organic vapor.

EYE PROTECTION: Safety glasses.

HAND PROTECTION: Impervious gloves. Long sleeved clothing. Remove and wash contaminated clothing before re-use. **OTHER PROTECTIVE EQUIPMENT:** No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Not determined

Physical State Liquid

Odor FAINT EPOXY ODOR

Odor threshold

pH

NON-AQUEOUS

Melting point / freezing point (°C)

Not determined

Boiling point/range (°C)

N.D. - N.D.

Flash Point, (°F / °C)

>485F / >251C

Evaporation rate Not determined

Flammability (solid, gas) Not determined

Upper/lower flammability or explosive N/A - N/A

limits

Vapour Pressure NOT DETERMINED

Vapour density

Relative density

Not determined

Solubility in / Miscibility with water

NEGLIGIBLE

Partition coefficient: n-octanol/water

Not determined

Auto-ignition temperature (°C)

Not determined

Decomposition temperature (°C)

Not determined

Viscosity N/A

Explosive properties Not determined

Oxidising properties

Not determined

9.2 Other information

VOC Content g/l: 5.0

Specific Gravity (g/cm3) 1.372

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed. Stable. Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Strong oxidizing agents. Acids and bases.

10.6 Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapours. Alcohols. Exothermic reaction. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information Inhalation LC50: No information

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
25068-38-6	PHENOL, 4,4'-(1- METHYLETHYLIDENE) BIS-, POLYMER WITH (CHLOROMETHYL) OXIRANE	>2000 mg/kg, rat, oral	>2000 mg/kg, rat		0.000	0.000
13463-67-7	titanium dioxide	10000 mg/kg, oral (rat)			0.000	6,82 mg/l (rat) 4h
100-51-6	Benzyl alcohol	1620 mg/kg, rat	2000 mg/kg, rabbit	4.178 mg/l, rat, 4h	0.000	4.178 mg/l,4h, rat

Additional Information:

This product is classified as a "Reproductive Toxicity - Category 2" due to containing a substance classified as a reproductive toxin via ingestion / oral exposure route only. Normal product application methods by trained crew members would not present a risk of oral exposure or ingestion. This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia): No information No information IC50 72hr (Algae): No information LC50 96hr (fish):

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Other adverse effects: No information

CAS-No.	<u>Chemical Name</u>	EC50 48hr	IC50 72hr	LC50 96hr
25068-38-6	PHENOL, 4,4'-(1-METHYLETHYLIDENE) BIS-, POLYMER WITH (CHLOROMETHYL) OXIRANE	1.8 mg/l	No information	1.3 mg/L
13463-67-7	titanium dioxide	>100 mg/l (EC50, 48h, Daphnia magna OECD202)ation	No information	>1000 mg/l
100-51-6	Benzyl alcohol	230 mg/l	700 mg/l	460 mg/l

13. Disposal Considerations

WASTE TREATMENT METHODS: If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1 UN number UN3082

14.2 UN proper shipping name Environmentally Hazardous Substance, Liquid, n.o.s. **Technical name** reaction product: bisphenol-a-(epichlorhydrin) epoxy resin

14.3 Transport hazard class(es)

Not applicable Subsidiary shipping hazard

14.4 Packing group

Not applicable 14.5 Environmental hazards 14.6 Special precautions for user Not applicable EmS-No.: F-A, S-F

Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC code

Not applicable

15. Regulatory Information

Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Carcinogenicity, Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

No SARA 313 substances exist in this product above de minimis concentrations.

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. Clean Air Act:

EPA Coating Category: TRAFFIC MARKING COATINGS

EPA VOC Content Limit (g/l): 150
Product VOC Content (g/l) 5.0

Thinning Recommendations: The coating is to be applied without thinning.

Application Recommendations: For professional use only.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u> CAS-No.

high molecular polymer 18275200000-5232

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

California Proposition 65:

^{*} As per the federal EPA definition for coating categories in 40 CFR 59.401.

^{**} Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

WARNING: Cancer - www.P65Warnings.ca.gov

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory or exempt.

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.

Reasons for revision

Composition Information Changed

Substance and/or Product Properties Changed in Section(s):

- 02 Hazard Identification
- 03 Composition/Information On Ingredients
- 09 Physical and Chemical Properties
- 11 Toxicological Information
- 14 Transportation Information
- 15 Regulatory Information

Substance Chemical Name Changed

Revision Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet updated national hazard communication standards which have adopted the provisions of the UN GHS system. There have been both formatting and content changes based on the GHS classification (if applicable), Please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.

- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

Classification, Labeling & Packaging Regulation

ЕC European Commission EH European Union United States US

CAS Chemical Abstract Service

European Inventory of Existing Chemical Substances EINECS

Registration, Evaluation, Authorization of Chemicals Regulation REACH

Globally Harmonized System of Classification and Labeling of Chemicals GHS

Long term exposure limit LTEL STEL Short term exposure limit Occupational exposure limit OEL

Parts per million ppm mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits VOC Volatile organic compounds

Grams per liter g/l

Milligrams per kilogram mg/kg

N/A Not applicable LD50 Lethal dose at 50%

Lethal concentration at 50% LC50

EC50 Half maximal effective concentration Half maximal inhibitory concentration IC50 Persistent bioaccumulative toxic chemical PBT Very persistent and very bioaccumulative

European Economic Community EEC

ADR International Transport of Dangerous Goods by Road RTD International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

International Bulk Container IBC RTT Respiratory Tract Irritation

NE Narcotic Effects

International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance

contains less than 0,1 % w/w benzene

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in

powder form containing 1 % or more of titanium dioxide which is in the form of

or incorporated in particles with aerodynamic diameter \leq 10 μm .

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product.

It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.